

## HIGH PERFORMANCE FLOORING WITH DESIGN IN MIND

Katanga brings you high performance flooring options with protective Cobalt Guard finish, providing superior scratch, scuff, and indentation resistance. Made with design and budget in mind, Katanga is your everyday flooring choice that combines contemporary style and durability for the highest foot traffic areas.




Arctic K12-804 / Loose Lay KP5-804




Polar K12-800 / Loose Lay KP5-800



Sand Dune K12-802 / Loose Lay KP5-802




Myrtle K12-801 / Loose Lay KP5-801




Macadamia K12-803 / Loose Lay KP5-803




Mineral K12-807 / Loose Lay KP5-807




Capetown K12-811 / Loose Lay KP5-811




Tundra K12-805 / Loose Lay KP5-805




Burro K12-812 / Loose Lay KP5-812



Caribou K12-808 / Loose Lay KP5-808




Armor K12-806 / Loose Lay KP5-806



Jet Set K12-809 / Loose Lay KP5-809



Oxford K12-813 / Loose Lay KP5-813




Bison K12-810 / Loose Lay KP5-810



Hare\* K12-815 / Loose Lay KP5-815



Geyser\* K12-816 / Loose Lay KP5-816




Hoot\* K12-814 / Loose Lay KP5-814




Shiitake\* K12-818 / Loose Lay KP5-818



Anchorage\* K12-819 / Loose Lay KP5-819



Boa\* K12-817 / Loose Lay KP5-817




Doe\* K12-821 / Loose Lay KP5-821



Whitecap\* K12-822 / Loose Lay KP5-822



Topsoil\* K12-820 / Loose Lay KP5-820



Grizzly\* K12-823 / Loose Lay KP5-823



## GLUE DOWN LVT TECHNICAL

ASTM F 970	Static Load Limit	Passes
ASTM F 925	Chemical Resistance	Passes
ASTM E 648	Critical Radiant Flux	Class I, >.45 w/cm <sup>2</sup>
ASTM E 662	Smoke Density	Passes, <450
ASTM F 1515	Light Stability	Passes
ASTM F 510	Wear Resistance	Wear Group: T
ASTM F 2199	Dimensional Stability	Passes
ASTM F 1914	Residual Indentation	Passes
DIN 51130	Slip Resistance	R10

## FEATURES/BENEFITS

- 7 Year Light Commercial Warranty
- 20 Year Residential Warranty
- Durability, dependability, and clean designs make Katanga LVT the right choice
- Katanga Glue Down LVT is finished with Cobalt Guard, an enhanced polyurethane finish, that provides superior scratch and scuffing resistance
- Cost effective LVT option that meets the needs of many of your flooring projects
- FloorScore® certified



## PACKAGING

Size:	Nominal 7" x 48" Planks, Square Edge
Gauge:	2mm
Wear Layer:	12mil
Finish:	Cobalt Guard (enhanced polyurethane)
Method of Install:	Glue Down
Carton Qty:	22 pieces per carton (51.39 sq ft)
Item/Color Identifier:	K12-###

*Standard 2mm 12mil in stock.  
Additional wear layer and  
thickness options available.*

## LOOSE LAY W/PERFORMANCE PAD TECHNICAL

ASTM F 970	Static Load Limit	Passes
ASTM F 925	Chemical Resistance	Passes
ASTM E 648	Critical Radiant Flux	Class I, >.45w/cm <sup>2</sup>
ASTM E 662	Smoke Density	Passes, <450
ASTM F 1515	Light Stability	Passes
ASTM F 510	Wear Resistance	Wear Group: T
ASTM F 2199	Dimensional Stability	Passes
ASTM F 1914	Residual Indentation	Passes
DIN 51130	Slip Resistance	R10
ASTM E 90/E 492	Acoustical Rating – 6" Concrete (No Ceiling)	IIC 53, STC 54, Delta IIC 20
Additional Sound Testing	Acoustical Rating – 6" Concrete (With Ceiling)	IIC 57

## FEATURES/BENEFITS

- Lifetime Residential Warranty
- 10-Year Commercial Warranty
- Glue Down Required for rolling load applications
- Simplicity in loose lay installation provides the ability to complete installation projects quickly, install over certain existing floors, and have removable and easily replaceable floors. Loose Lay can be installed via standard loose lay installation methods or fully adhered with approved adhesive.
- Katanga Loose Lay is constructed with an attached Performance Pad that provides additional sound control properties while also adding a non-skid backing
- Katanga Loose Lay's gauge and installation methods coordinate well when paired with carpet or carpet tile on an installation
- Katanga Loose Lay is constructed with Cobalt Guard, an enhanced polyurethane finish, that provides superior scratch and scuffing resistance
- FloorScore® certified



## PACKAGING

Size:	Nominal 7" x 48" Planks, Square Edge
Gauge:	5mm
Wear Layer:	20mil
Finish:	Cobalt Guard (enhanced polyurethane)
Method of Install:	Loose Lay
Carton Qty:	10 pieces per carton (23.36 sq ft)
Item/Color Identifier:	KP5-###

*Standard 5mm 20mil LL w/Pad in stock.  
Additional wear layer and thickness options available.*