

# TANGENT LVT

LUXURY VINYL TILE



## FEATURES/BENEFITS

- 15-year commercial warranty,
- Limited lifetime residential wear warranty
- Manufactured and stocked in the USA
- 20 forward thinking colors/patterns that set the tone for inspired designs
- Cobalt Guard provides an enhanced polyurethane finish that withstands the toughest commercial settings
- Standard construction is 2.5mm 20mil glue down; choose from other special order constructions – other glue down options, loose lay, and click constructions
- Eco-Focused – FloorScore certified, anti-bacterial, non-phthalate plasticizers used in manufacturing, and 100% recyclable



Sequoia T20-610



Cohiba T20-607



Cedar Bark T20-608



French Press T20-615



Run Raisin T20-609



Petrified Shale T20-604



Ginger T20-606



Sahara Desert T20-611



Nut Butter T20-612



Whole Wheat T20-605




Monument T20-602



Crystal T20-613



Grey Abyss T20-614



Cast Iron T20-601



Charcoal T20-600



Steel Cast T20-603



Crosswinds T20-616



Safari T20-618



Silver Ore T20-617



Sea Otter T20-619



# TANGENT LVT

LUXURY VINYL TILE



## TECHNICAL

Nominal Dimensions	7" x 48" Planks	CAN/ULC - S102.2 - Surface Burning	50, 150 SDC
Gauge	2.5mm	ASTM D2047 - Slip Resistance	> 0.60
Finish Texture	Embossed	ASTM F970 - Static Load Limit	Passes, > 250 psi
Wear Layer Thickness	20mil	ASTM F970 (Modified) - Max Weight	2000 psi (<.005" Indentation)
Quantity Per Carton	15 Planks / 34.84 sq ft per ctn	ASTM F925 - Chemical Resistance	Excellent (Chart available)
Leed V2009 Credit 6 RRM Content	12%	ASTM F1515 - Light Stability	Passes
Leed V2009 IEQ Credit 4.1	Qualifies	ASTM F1914 Residual Indentation	Passes
Leed V2009 IEQ Credit 4.3	Qualifies	ASTM F2199 Dimensional Stability	Passes
ASTM F1700 - Solid Vinyl Tile	Class III, Type A + B	Acclimation Time	48 Hours
ASTM E648 - Critical Radiant Flux	Class I, >.45 w/cm <sup>2</sup>	Storage + Acclimation Temperature	65-85 Degrees Fahrenheit
ASTM E662 - Smoke Density	Passes, <450		

## PACKAGING

### STANDARD PRODUCT:

Size:	Nominal 7" x 48" Planks
Gauge:	2.5mm
Wear Layer:	20mil

Finish:	Cobalt Guard (enhanced polyurethane)
Method of Install:	Glue Down
Carton Qty:	15 pieces per carton (34.84 sq ft)
Item/Color Identifier:	T20-###

### PACKAGING FOR SPECIAL ORDER PRODUCTS:

Size:	7.08" x 47.24" Planks
Gauge:	2mm
Wear Layer:	6mil
Finish:	Cobalt Urethane
Method of Install:	Glue Down
Carton Qty:	18 pieces per carton (41.81 sq ft)
Item/Color Identifier:	T06-###

Size:	7.08" x 47.24" Planks
Gauge:	4mm
Wear Layer:	20mil
Finish:	Cobalt Guard (enhanced polyurethane)
Method of Install:	Loose Lay
Carton Qty:	10 pieces per carton (23.23 sq ft)
Item/Color Identifier:	TL4-###

Size:	7.08" x 47.24" Planks
Gauge:	2mm
Wear Layer:	12mil
Finish:	Cobalt Urethane
Method of Install:	Glue Down
Carton Qty:	18 pieces per carton (41.81 sq ft)
Item/Color Identifier:	T12-###

Size:	7.08" x 47.24" Planks
Gauge:	5mm
Wear Layer:	20mil
Finish:	Cobalt Guard (enhanced polyurethane)
Method of Install:	Loose Lay
Carton Qty:	10 pieces per carton (23.23 sq ft)
Item/Color Identifier:	TL5-###

Size:	7.28" x 47.72" Planks
Gauge:	4mm
Wear Layer:	20mil
Finish:	Cobalt Guard (enhanced polyurethane)
Method of Install:	Click
Carton Qty:	10 pieces per carton (24.13 sq ft)
Item/Color Identifier:	TCK-###

Contact your Cobalt Surfaces Rep for minimum order requirements and approximate lead times on special order products.



## TANGENT LVT

LUXURY VINYL TILE

