

Declare. SM

Durat Standard Collection Durat Solid Surfaces

Final Assembly: Norcross, Georgia, USA

Life Expectancy: 15+ Year(s)

End of Life Options: Take Back Program (Durat Circular),
Recyclable (100%)

Ingredients:

FLAME RETARDANT: Aluminum hydroxide; **Binder:** POLYESTER; **Filler:** Polymethyl methacrylate; **Catalyst:** MEK Peroxide; **Pigment:** Titanium dioxide; Polyester diurethane methacrylate resin based dialkyldiol/adipic acid polyester diol with toluene diisocyanate and hydroxyethyl methacrylate; **Additive :** Aromatic 100 (Aromatic naphtha, type 1); Butylated hydroxytoluene (BHT)

Living Building Challenge Criteria:

I-13 Red List:

- | | |
|---|-----------------------------|
| <input checked="" type="checkbox"/> LBC Red List Free | % Disclosed: 100% at 100ppm |
| <input type="checkbox"/> LBC Red List Approved | VOC Content: Not Applicable |
| <input type="checkbox"/> Declared | |

I-10 Interior Performance: Not Compliant

I-14 Responsible Sourcing: Not Applicable

DRA-0001

EXP. 01 JAN 2024

Original Issue Date: 2022