




WINEO PURLINE IS AN ENTIRELY NEW CLASS OF FLOORING PRODUCED WITH NATURAL RAW MATERIALS.



wineo PURline is made with plant-based oils and naturally occurring mineral components.

The ingredients are combined to create an extremely dense bio-polyurethane that is non-porous, stain resistent and durable.



CANOLA OIL from rappa seed



CASTOR OIL from castor seed



WINEO PURLINE IS FLOORING REINVENTED.



PURline is not LVT; it's a completely new type of flooring. 5x more durable than vinyl flooring products, PURline stands up to wear and tear, easily.



PURline's proprietary bio-polyurethane creates healthier environments, naturally.



PURline is the only flooring that can endure the extreme demands of healthcare, hospitality, retail and public buildings, beautifully.

With unparalleled environmental credentials.











FLOATING WOOD SNOW



MISSOURI OAK



MIDNIGHT GREY



HALIFAX OAK



SINAI SAND



PACIFIC OAK



TERRACOTTA DARK



PURE WHITE STARS



PACIFIC OAK



SILVER GREY









Pure White

Honey Mustard

Terracotta Dark

Red Rubin



Apple Green



Jungle Green



Racing Green


Purple Rain




Summer Sky



Navi Blue




Navi Blue Stars



Denim Blue Stars





Pure White Stars

Sinai Sand



Sinai Sand Stars



Melange










Cappuccino

Light Grey

Silver Grey


Silver Grey Stars



Steel Grey



Midnight Grey



Midnight Grey Stars



Pure Black Stars



Floating Wood Snow



Floating Wood Sand



Napa Walnut Cream



Napa Walnut Brown



Halifax Oak



Pacific Oak



Cottage Oak

Missouri Oak









Specifications

| Material | Heterogeneous commercial floor covering consisting of bio-polyurethane (ecuran), glass fiber reinforcement, paper print layer, and clear PU top layer (This product contains no PVC) |
|---|--|
| Backing | FleeceTEC System® |
| Total Weight | 0.74 lbs/sq ft |
| Sizes | Wood XS: ~ 4" x 24" Wood L: ~ 8" x 48" Wood XL: ~ 10" x 59" Stone XL: ~ 20" x 39" |
| Overall Thickness | 2.5 mm |
| Sound Transmission (ASTM E2179) | Δ (Delta) IIC 7 |
| Color & Light Stability (ASTM F1515 and F1514) | Δ (Delta) E value of <0.1 with <0.8 being required |
| Burning Characteristics (ASTM E648 and E662) | Meets Class 1 |
| Static Load (ASTM F970) | Exceeds requirement at 1450 psi |
| Warranty | 10 Years |
| | |

For CSI specifications and the most up-to-date documentation, please visit our website at purline-contract.com.

ecuran is made with bio-polyurethane manufactured with plant-based oils and mineral components.



Declare.

PURLINE Resilient Polyurethane Floor Covering

Windmöller GmbH

Final Assembly: Detmold, Germany Life Expectancy: 20 Years End of Life Options: Landfill (100%)

Ingredients:

Polymer: Polyurethane; Filler: Calcium Carbonate, Zeolite; Flame Retardant: Aluminum Hydroxide; Additives and Decor Paper Dyes: Undisclosed (0.5-1.0%); Foam Regulator: White Oil; Nonwoven: Polypropylene, Polyester, Glass; Decor Paper: Cellulose; Decor Paper Filler: Kaolin; Decor Paper Pigment: Titanium Dioxide

¹LBC Temp Exception I10-E4 Proprietary Ingredients <1%

Living Building Challenge Criteria:



EXP. 01 JAN 2021 VOC Emissions: CDPH Compliant LBC Red List Free LBC Compliant Declared

MANUFAGTURER CLAIMS VERIFIED BY WAP Sustainability INTERNATIONAL LIVING FUTURE INSTITUTE¹⁶¹ de

wineo PURLINE

800-628-7462 | purline-contract.com

© 2021 Matter Surfaces. All rights reserved.